

Infini V4 WP



- IP65 waterproof and dustproof
- Dual outputs for smart load management
- Self-consumption and Feed-in to the grid
- Programmable supply priority for PV, Battery or Grid
- Built-in communication port for BMS (RS485)
- User-adjustable charging current and voltage
- Programmable multiple operation modes: Grid-tie, off-grid and grid-tie with backup
- Parallel operation up to 9 units

Infini V4 WP Hybrid Inverter Specification

MODEL	Infini V4 WP 6kw
PHASE	1-phase in / 1-phase out
MAXIMUM PV INPUT POWER	7000W
RATED OUTPUT POWER	6000VA/6000W
MAXIMUM CHARGING POWER	6000 W
GRID-TIE OPERATION	
PV INPUT (DC)	
Maximum DC Voltage	550 VDC
Start-up Voltage / Initial Feeding Voltage	120VDC / 150 VDC
MPP Voltage Range	120 VDC ~ 450 VDC
Number of MPP Trackers / Maximum Input Current	1 / 30A
GRID OUTPUT (AC)	
Nominal Output Voltage	220/230/240 VAC
Output Voltage Range	184 - 264.5 VAC or 195.5 - 253 VAC or 184 - 264.4 VAC (Selectable)
Nominal Output Current	26A
Power Factor	> 0.99
EFFICIENCY	
Maximum Conversion Efficiency (DC/AC)	97%
OFF-GRID OPERATION	
AC INPUT	
AC Start-up Voltage / Auto Restart Voltage	120 - 140 VAC / 180 VAC
Acceptable Input Voltage Range	90 - 280 VAC or 170 - 280 VAC
Frequency Range	50 Hz/60 Hz (Auto sensing)
Maximum AC Input Current	40 A
PV INPUT (DC)	
Maximum DC Voltage	550 VDC
MPP Voltage Range	120VDC ~ 450 VDC
Number of MPP Trackers / Maximum Input Current	1 / 30A
BATTERY MODE OUTPUT (AC)	
Nominal Output Voltage	220/230/240 VAC
Output Waveform	Pure sine wave
Efficiency (DC to AC)	93%
HYBRID OPERATION	
PV INPUT (DC)	
Maximum DC Voltage	550 VDC
Start-up Voltage / Initial Feeding Voltage	120 VDC / 150 VDC
MPP Voltage Range	120 VDC ~ 450 VDC
Number of MPP Trackers / Maximum Input Current	1 / 30A
GRID OUTPUT (AC)	
Nominal Output Voltage	220/230/240 VAC
Output Voltage Range	184 - 264.5 VAC or 195.5 - 253 VAC or 184 - 264.4 VAC (Selectable)
Nominal Output Current	26A
AC INPUT	
AC Start-up Voltage / Auto Restart Voltage	120 - 140 VAC / 180 VAC
Acceptable Input Voltage Range	90 - 280 VAC or 170 - 280 VAC
Maximum AC Input Current	40 A
BATTERY MODE OUTPUT (AC)	
Nominal Output Voltage	220/230/240 VAC
Efficiency (DC to AC)	93%
BATTERY & CHARGER	
Nominal DC Voltage	48 VDC
Maximum Solar Charging Current	120 A
Maximum AC Charging Current	120 A
Maximum Charging Current	120 A
GENERAL	
PHYSICAL	
Dimension, D x W x H (mm)	192 x 360 x 665
Net Weight (kgs)	22.5
INTERFACE	
Parallel Function	Yes, 9 units
Communication Port	USB or RS-232/Dry Contact/RS485/Wi-Fi
ENVIRONMENT	
Humidity	0 ~ 95% RH (No condensing)
IP degree	IP65
Operating Temperature	-25°C to 50°C

Product specifications are subject to change without further notice.