

LIO II-4810 is Lithium-ion battery module specially designed for energy storage system with 48V system

- Lithium Iron Phosphate (LFP) cell guarantees safety and reliability
- Easy to install on the floor
- Suitable for wide range of inverters with 48V system



UN 38.3 **UK
CA**



Compact size and Lightweight

Built-in Lithium Iron Phosphate (LFP) cell with less space and weight.



Fast charging

Battery module can be fully charged in shorter time.



Modular design for easy scalable


Battery module can be easily stacked and added for energy expansion.




Maximum Lifecycle

8000 cycles is for 60% DOD with >50% capacity
4000 cycles is for 90% DOD with >80% capacity

System Diagram



Technical Selection Guide



Battery Module	LIO II-4810 (5 kwh, 51.2V)			
Battery Cell Technology	Lithium Iron Phosphate			
Applicable Inverter Rating	≤ 5.6 kw			
Number of Module	1	2	3	4
Usable Energy	5 kwh	10 kwh	15 kwh	20 kwh
Rated Discharging Current	150 A	150 A	150 A	150 A
Peak Discharging Current	192 A, 1 min	192 A, 1 min	192 A, 1 min	192 A, 1 min
Nominal Voltage	51.2 V	51.2 V	51.2 V	51.2 V
Operating Voltage	40 -56 VDC	40 -56 VDC	40 -56 VDC	40 -56 VDC
Charging Current	100A Max, 30A Default	100A Max, 30A Default	100A Max, 30A Default	100A Max, 30A Default
Dimension, D x W x H (mm) without feet	185 x 540 x 420	185 x 540 x 840	185 x 540 x 1260	185 x 540 x 1680
Net Weight (kg)	48	96	144	192



Battery Module	LIO II-4810 (5 kwh, 51.2V)		
Battery Cell Technology	Lithium Iron Phosphate		
Applicable Inverter Rating	6 kw ~ 12 kw		
Number of Module	2	3	4
Number of PDU Module	1	1	1
Usable Energy	10 kwh	15 kwh	20 kwh
Rated Discharging Current	300 A	300 A	300 A
Peak Discharging Current	384 A, 1 min	384 A, 1 min	384 A, 1 min
Nominal Voltage	51.2 V	51.2 V	51.2 V
Operating Voltage	40 - 56 VDC	40 - 56 VDC	40 - 56 VDC
Dimension, D x W x H (mm) without feet	185 x 540 x 1040	185 x 540 x 1460	185 x 540 x 1880
Net Weight (kg)	102	150	198

General Specification

Operation Temperature	Charge	0°C~50 °C
	Discharge	0°C~50 °C
Storage Temperature (At 50% SOC and specified temp, recoverable capacity in % vs time / 50%)		< 18 months: -20°C~25 °C
		< 3 months: 25°C~45 °C
		< 1 months: 45°C~60 °C
		20°C ± 5 °C is the recommended storage temperature
IP Protection		IP20
Communication		RS485 port (RJ45), CAN
Certifications		IEC 62619, EN 61000-6-3, EN 61000-6-1, UKCA, UN38.3

Product specifications are subject to change without further notice.